SSOBCB03

SOMERSBY Shower Range

Somersby Exposed Shower Valve with Bottom Outlet Connection





Specification				
Main Construction Material:	Brass			
No of Controls:	2			
Shower Type:	Exposed Thermostatic Shower			
Handle Type:	Crosshead			
Valve/Cartridge Type:	Thermostatic Cartridge			
Maximum Hot Water Supply Temperature °C:	65			
Maximum Static Pressure: (bar)	10			
Plumbing System Suitability:	All - Ideally Balanced			
Working Pressure Range:	Min. 0.2 Bar, max. 5.0 Bar			
Connection Inlet:	15mm Compression			
Connection Outlet:	15mm Compression			
Isolation Valve Included:	No			
Check Valve Included:	Yes			

Dimensions (measurements in mm)


Features:


- Optimised for UK market, designed to work at pressure range of 0.1 - 5.0 bar
- Thermostatic temperature control and automatic stop prevent surges of hot or
- Performance Flow to provide a drenching experience
- Adjustable inlet centres, allowing you to use existing pipework with centres measuring anything between 138mm and 158mm.
- Exposed

Product Certifications:



Additional Information:





Flow Rates (I/min)								
System Pressure (bar)	0.2	0.5	I	2	3	5		
Through Handset (mixed)		11.8	14.1	13.8	13.6	10.6		

TECHNICAL DATA SHEET YEAR



