SHDAB02

HARTLEBURY Shower Range

Hartlebury Exposed Shower Valve with Bottom Outlet Connection Vintage Gold



| F | ea | tu | re | S: |
|---|----|----|----|----|
| | | | | |

- Optimised for UK market, designed to work at pressure range of 0.1 - 5.0bar
- Thermostatic temperature control and automatic stop prevent surges of hot or cold water
- Performance Flow to provide a drenching experience
- Adjustable inlet centres, allowing you to use existing pipework with centres measuring anything between 136mm and 158mm.

Product Certifications:





WRAS Certificate No: 2205916 WRAS Expiry Date: 31/07/2027

Additional Information:

| Specification | | | | | | |
|---|-----------------------------------|--|--|--|--|--|
| Finish/Colour: | Gold Plated | | | | | |
| Main Construction Material: | Brass | | | | | |
| No of Controls: | 1 | | | | | |
| Shower Type: | Exposed Concentric | | | | | |
| Shower Head Type: | None | | | | | |
| Shower Kit: | None | | | | | |
| Valve/Cartridge Type: | Concentric Cartridge | | | | | |
| Maximum Hot Water Supply Temperature ^o C: | 65 | | | | | |
| Plumbing System Suitability: | Suitable for all plumbing systems | | | | | |
| Minimum Dynamic Pressure (bar): | 0.1 | | | | | |
| Maximum Dynamic Pressure (bar): | 5 | | | | | |
| Maximum Static Pressure (bar): | 10 | | | | | |
| Connection Inlet: | 15mm Compression | | | | | |
| Connection Outlet: | G 1/2" | | | | | |
| Isolation Valve Included: | No | | | | | |
| Check Valve Included: | Yes | | | | | |

Dimensions (measurements in mm)





| Flow Rates (l/min) | | | | | | | | | |
|-----------------------|------|------|------|------|------|------|--|--|--|
| System Pressure (bar) | 0.1 | 0.5 | 1 | 2 | 3 | 5 | | | |
| Valve Only (mixed) | 6.08 | 13.5 | 13.6 | 14.9 | 15.1 | 15.4 | | | |

Technical Data Sheet





Da