# GLASTONBURY Tap Range

Glastonbury 3TH Swivel Spout Brushed Nickel



Specification					
Product Type:	Bathroom Tap				
Main Construction Material:	Brass				
Mount Type:	Deck Mounted				
Handle Type:	Lever Handles				
Connection Inlet:	G 1/2" BSP				
Connection Outlet:	Flow Straightener				
Number of Tap Holes:	3				
Valve/Cartridge Type:	1/4 Turn 1/2" Ceramic Disc Valve				
Plumbing System Requirements:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.4 bar				
Maximum Dynamic Pressure (bar):	5.0 bar				
Maximum Hot Water Temperature °C:	60°C				
Maximum Static Pressure (bar):	10 bar				
Flow Type:	Single Flow				
Isolation Included:	No				

#### Features:

- Everything you need in the box including flexible tails and pop-up waste so nothing to buy separately.
- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- On trend brushed nickel finish.
- 10 year parts and I year labour guarantee for peace of mind.
- Also available in other finishes.
- Co-ordinating Bathroom taps, Recess shower and Accessories available.

#### **Product Certifications:**



**₫**71.4 l/min

### Additional Information:

212 160	
125 165	<del>-</del>
85	<b>Ū</b> 72
45	
50	

Dimensions (measurements in mm)

Flow Rates (I/min)								
System Pressure (bar)	0.4	0.5	1	2	3	5		
TGRCN09 (mixed)	26.9	29.4	42. I	58.7	71.4	90.5		

## **TECHNICAL DATA SHEET**



