## TTRCC01

### TRINITY Tap Range Trinity Bath Pillar Taps Chrome



Specification					
Product Type:	Bathroom Taps				
Main Construction Material:	Brass				
Mount Type:	Deck Mounted				
Handle Type:	Crosshead Handles				
Connection Inlet:	3/4" BSP Connections				
Connection Outlet:	Open				
Number of Tap Holes:	2				
Valve/Cartridge Type:	3/4" Long Stem Ceramic Disc Valves				
Plumbing System Requirements:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.2 bar				
Maximum Dynamic Pressure (bar):	5.0 bar				
Maximum Hot Water Temperature °C:	65°C				
Maximum Static Pressure (bar):	10 bar				
Isolation Included:	No				

## Features:


- Uniquely designed Timeless detailing for traditional bathrooms.
- Hand-finished handles using precision watchmaker techniques.
- Metal fixing nut for added durability


#### **Product Certifications:**

Water Label	\$32.88l/min

#### Additional Information:

Dimensions	(measurements	in	mm)	
------------	---------------	----	-----	--





Flow Rates (I/min)								
System Pressure (bar)	0.2	0.5	I	2	3	5		
TTRCC01 (Cold)	8.22	13.08	18.78	26.7	32.88	42		
TTRCC01 (Hot)								

# TECHNICAL DATA SHEET





Heritage Bathrooms, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Telephone: 0330 026 8503. Web Site: www.heritagebathrooms.com Email: technical@heritagebathrooms.com. \*10 year guarantee applies to products purchased on or after 01/04/2021. Non-chrome product finishes carry a 3 year guarantee on finish. All of our products are covered by a guarantee. Most include both parts and labour. Please note that guarantees are only valid with a proof of purchase. Our guarantees apply to products in domestic use. Any products in commercial use carry a guarantee of 1 year. See www.heritagebathrooms.com/warranty for more information. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Heritage Bathrooms pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.